



AFTERBURNER ASHING FURNACE ABF

The ABF Afterburner Ashing Furnace is particularly suitable for ashing larger samples or materials such as biomass, which are likely to generate substantial amounts of smoke. The furnace comprises a large main combustion chamber equipped as standard with a two tier set of sample baskets. The exhaust from the main chamber is processed through a high temperature afterburner designed to further process fumes and smoke.

STANDARD FEATURES

- | 800°C maximum operating temperature - ashing chamber
- | 28 Litre chamber volume
- | Afterburner rated for up to 40 g carbon per ashing load
- | Two tier baskets with loading tray and handle
- | Programmable EPC3016P1 controller
- | Independent control of afterburner temperature up to 950°C
- | Silicon carbide shielded wire wound elements
- | Supplied with 3-phase supply as standard
- | Ethernet communications

OPTIONS (*SPECIFY THESE AT TIME OF ORDER*)


- | A range of sophisticated digital controllers, multisegment programmers and data loggers with digital communication options is available - more information about controllers
- | Over-temperature protection (recommended to protect valuable contents & for unattended operation)
- | Optional floor stand

AFTERBURNER ASHING FURNACE ABF

TECHNICAL DETAILS

Airflow in the ABF 8/28 Ashing Furnace

1. Air inlet – air is preheated before entering the chamber
2. Air inlet into afterburner to ensure complete combustion
3. Air inlet into plenum to cool the gases before entering the extraction fan
4. Chimney
5. Furnace chamber
6. Afterburner
7. Extraction fan
8. Two tier perforated basket system



Airflow Diagram

TECHNICAL DETAILS (MODELS)

	ABF 8/28
Max temp (°C)	800
Max continuous operating temp (°C)	700
Dimensions: Internal H x W x D (mm)	210 x 290 x 445
Dimensions: External H x W x D (mm)	980 x 600 x 750
Dimensions: Height to top chimney (mm)	1150
Configuration	Bench-top
Volume (litres)	28
Max power (W)	8000
Holding power (W)	3828
Thermocouple type	K
Weight (kg)	120

Please note

- Holding power is measured at 500°C
- Heat up rate is measured to 100°C below max, using an empty chamber

www.carbolite.com/abf